



## Fender set for Catrike

Big Cat HPV. LLC  
720 Business Park Blvd Ste 22  
Winter Garden, FL 34787

### PARTS LIST:

- 2 Front Fenders
- 1 Rear Fender (larger)
- 2 Fender mounting brackets
- 6 Fender Stays with Clips
- 2 M5X15 socket head cap screws
- 2 M5x10 Buttonhead screws
- 2 M5 Nylon Locknuts
- 2 Well Nuts
- 2 ¼" x 1-1/2" Screws

For Pocket and Speed:

- 2 M6x40 socket head cap screws



### To install the front fenders:

*Note: The mounting bracket has two holes in it, one slightly larger than the other. The end with the smaller hole attaches to the top of the fender while the end with the larger hole sits on top of the headset.*

1. Using an M5x10 screw and locknut, attach the front fender to the mounting bracket.



2. Remove the screw only from the headset. Place the mounting bracket on top of the headset and replace the screw with the M6x40 provided to secure it in place, making sure the fender is aligned and centered above the tire.



*Note: If you are installing fenders on the Road model, you can re-use the screw removed from the headset.*

## Fender set for Catrike

3. Insert the well nut into the outside hollow end of the axle.  
A little soapy water will help you slide it into place.

*Note: Make sure the axle nut is securely tightened before inserting the well nut.*



4. Put the 1/4"x1 1/2" screw through the eye of a fender stay, then screw it into the well nut. Allow the soapy water to dry before you tighten the bolt or you may cause the well nut to slip back out of the axle.

5. Slide the fender clip over the edge of the fender. You may have to bend the stay in towards the tire slightly to keep the fender aligned and centered over the tire.



6. Tighten the screws on the stay clips.

7. Repeat for the other side, making sure to attach the mounting bracket to the fender on the other side.

### To install rear fender:

1. Using the M5x15 screws, attach the fender stays to the holes provided in the frame above the dropouts.  
Two fender stays go on each side of the rear wheel.



2. Attach the fender stay clips to the fender and tighten the screws.

